

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Isoamyl alcohol

Product Number : W205710
Brand : Aldrich

Supplier : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832
Fax : +1 800-325-5052
Emergency Phone # (For both supplier and manufacturer) : (314) 776-6555

Preparation Information : Sigma-Aldrich Corporation
Product Safety - Americas Region
1-800-521-8956

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Combustible Liquid, Target Organ Effect, Irritant

Other hazards which do not result in classification

May form explosive peroxides.

GHS Classification

Flammable liquids (Category 3)
Acute toxicity, Inhalation (Category 4)
Acute toxicity, Dermal (Category 5)
Skin irritation (Category 2)
Eye irritation (Category 2A)

GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Hazard statement(s)

H226 Flammable liquid and vapour.
H313 May be harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.

Precautionary statement(s)

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

HMIS Classification

Health hazard: 2
Chronic Health Hazard: *
Flammability: 2

| | |
|---------------------------|---|
| Physical hazards: | 0 |
| NFPA Rating | |
| Health hazard: | 2 |
| Fire: | 2 |
| Reactivity Hazard: | 0 |

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : 3-Methyl-1-butanol
 Isoamyl alcohol
 Isopentyl alcohol

Formula : C₅H₁₂O
 Molecular Weight : 88.15 g/mol

| Component | Concentration |
|---------------------------|---------------|
| 3-Methylbutan-1-ol | |
| CAS-No. | 123-51-3 |
| EC-No. | 204-633-5 |
| Index-No. | 603-006-00-7 |
| | <= 100 % |

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Hazardous decomposition products formed under fire conditions. - Nature of decomposition products not known.

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value | Control parameters | Basis |
|--------------------|------------------------------------------------|-------|----------------------------------|----------------------------------------------------------------------------------|
| 3-Methylbutan-1-ol | 123-51-3 | TWA | 100 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| Remarks | Eye & Upper Respiratory Tract irritation | | | |
| | | STEL | 125 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | Eye & Upper Respiratory Tract irritation | | | |
| | | TWA | 100 ppm 360 mg/m ³ | USA. NIOSH Recommended Exposure Limits |
| | | ST | 125 ppm 450 mg/m ³ | USA. NIOSH Recommended Exposure Limits |
| | | TWA | 100 ppm 360 mg/m ³ | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| | The value in mg/m ³ is approximate. | | | |

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 30 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

| | |
|--------|---------------|
| Form | liquid, clear |
| Colour | colourless |

Safety data

| | |
|----------------------------------------|---------------------------------------------------------------------------|
| pH | 5.6 at 25 g/l at 20 °C (68 °F) |
| Melting point/freezing point | Melting point/range: -117 °C (-179 °F) - lit. |
| Boiling point | 130 °C (266 °F) - lit. |
| Flash point | 43 °C (109 °F) - closed cup |
| Ignition temperature | 340 °C (644 °F) |
| Auto-ignition temperature | no data available |
| Lower explosion limit | 1.2 %(V) |
| Upper explosion limit | 9 %(V) |
| Vapour pressure | 3 hPa (2 mmHg) at 20 °C (68 °F) 23.6 hPa (17.7 mmHg) at 50 °C (122 °F) |
| Density | 0.809 g/cm ³ at 25 °C (77 °F) |
| Water solubility | soluble |
| Partition coefficient: n-octanol/water | log Pow: 1.28 |
| Relative vapour density | 3.04 - (Air = 1.0) |
| Odour | no data available |
| Odour Threshold | no data available |
| Evaporation rate | no data available |

10. STABILITY AND REACTIVITY

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

no data available

Conditions to avoid

Heat, flames and sparks.

Materials to avoid

Strong oxidizing agents, Acid chlorides, Acid anhydrides, Reducing agents

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Hazardous decomposition products formed under fire conditions. - Nature of decomposition products not known.

Other decomposition products - no data available

11. TOXICOLOGICAL INFORMATION**Acute toxicity****Oral LD50**

LD50 Oral - rat - > 5,000 mg/kg

Inhalation LC50

LC50 Inhalation - rat - male and female - 6 h - > 14 mg/l

Dermal LD50

LD50 Dermal - rabbit - > 3,000 mg/kg

Other information on acute toxicity

no data available

Skin corrosion/irritation

Skin - rabbit - Skin irritation

Serious eye damage/eye irritation

Eyes - rabbit - Eye irritation

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

no data available

Teratogenicity

no data available

Specific target organ toxicity - single exposure (Globally Harmonized System)

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

no data available

Aspiration hazard

no data available

Signs and Symptoms of Exposure

prolonged or repeated exposure can cause: Nausea, Headache, Vomiting, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects

no data available

Additional Information

RTECS: EL5425000

12. ECOLOGICAL INFORMATION**Toxicity**

Toxicity to daphnia and other aquatic invertebrates EC50 - Daphnia magna (Water flea) - 260 mg/l - 48 h

Toxicity to algae EC50 - Desmodesmus subspicatus (green algae) - 490 mg/l - 72 h

Persistence and degradability

Biodegradability Result: > 70 % - Readily biodegradable.

Bioaccumulative potential

no data available

Mobility in soil

no data available

PBT and vPvB assessment

no data available

Other adverse effects

no data available

13. DISPOSAL CONSIDERATIONS**Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION**DOT (US)**

UN number: 1105 Class: 3 Packing group: III

Proper shipping name: Pentanols

Marine pollutant: No

Poison Inhalation Hazard: No

IMDG

UN number: 1105 Class: 3 Packing group: III EMS-No: F-E, S-D

Proper shipping name: PENTANOLS

Marine pollutant: No

IATA

UN number: 1105 Class: 3 Packing group: III

Proper shipping name: Pentanols

15. REGULATORY INFORMATION

OSHA Hazards

Combustible Liquid, Target Organ Effect, Irritant

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

| | CAS-No. | Revision Date |
|--------------------|----------|---------------|
| 3-Methylbutan-1-ol | 123-51-3 | 2007-03-01 |

Pennsylvania Right To Know Components

| | CAS-No. | Revision Date |
|--------------------|----------|---------------|
| 3-Methylbutan-1-ol | 123-51-3 | 2007-03-01 |

New Jersey Right To Know Components

| | CAS-No. | Revision Date |
|--------------------|----------|---------------|
| 3-Methylbutan-1-ol | 123-51-3 | 2007-03-01 |

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION**Further information**

Copyright 2013 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.
